

FULL BULLNOSE CUTTER VACUUM BRAZED

UNSUITABLE

IDEALLY SUITED

MATERIALS

ASPHALT OVER CONCRETE BRICKS - CLASS A ENGINEERING BRICKS - CLASS B ENGINEERING BRICKS - STANDARD FACING BRICKS CEMENT FIBRE BOARD

ALUMINIUM ASPHALT

CLAY PRODUCTS

COMPOSITE CLADDING & PANELS CONCRETE - BEAMS, KERBS, PIPES & SLABS

CONCRETE - BLOCK PAVING CONCRETE - FLAG STONES CONCRETE - FLINT AGGREGATE CONCRETE - GENERAL PURPOSE CONCRETE - GREEN (up to 24 Hours Old) CONCRETE - HEAVY STEEL REINFORCEMENT CONCRETE - LIGHT STEEL REINFORCEMENT

CONCRETE - ROOF TILES

CEMENT SCREED

GRITSTONE

LIMESTONE

MORTAR RAKING

QUARTZ WORKTOPS

RAILWAY SLEEPERS

TILES - CERAMIC TILES - GRANITE

TILES - LIMESTONE

TILES - PORCELAIN

TILES - MARBLE

TILES - SLATE TREE ROOTS

YORK STONE

SANDSTONE - ABRASIVE

STEEL SECTION - PIPES & BARS

TILES - 20mm EXTERIOR PORCELAIN

EARTHSTONE WORKTOPS

GLASS REINFORCED PLASTIC (GRP)

GRANITE - BLOCKS & WORKTOPS

GROUNDWORK - HARD SOIL

MARBLE - BLOCKS & WORKTOP

PLASTIC (PVC, PE, PP, PC & COMPOSITES)

LAMINATED PRODUCTS

CONCRETE BLOCKS - LIGHTWEIGHT 3 TO 7 NEWTON

CONCRETE BLOCKS - SOLID DENSITY 12+ NEWTON

CONCRETE BLOCKS - MEDIUM DENSITY 7 TO 12 NEWTON

OCCASIONAL USE







DESCRIPTION:

The vacuum brazed P5-VBBN is designed to add a full bullnose decorative finish to the edge of tiles and stone, such as exterior porcelain tiles, limestone, sandstone, quartz and granite up to 20mm thick. Whether you are creating a safe rounded edge to a step or a finished edge to a work surface, or coping stone, the M14 fitting allows the P5-VBBN to be fitted directly to any popular angle grinder, making it easy and practical to use.

DIMENSIONS PART NO.

DP16450 75 x 20mm x M14

PACKAGING DETAILS:

White cardboard box with information label



Widely Recycled

FEATURES:

- High quality, hard wearing vacuum brazed diamonds
- High resistance to heat build up
- M14 direct fitting

MACHINE SUITABILITY:

Electric and cordless angle grinders

USER TIPS:

- · Always wear the appropriate PPE
- Ensure that the P5-VBBN is suitable for the application
- Remove all flanges from the angle grinder and fully thread the P5-VBBN onto the exposed M14
- Move the cutter smoothly and in a single pass across the length of the cut - repeat until the desire finish is achieved
- Finish with a P5-BNSP Bullnose sanding pad



🖾 sales@premierdiamondproducts.co.uk 🗘 +44 (0) 1227 711 555









