



CLEAN WOOD & PVC REVERSE CUT JIGSAW BLADE (T-SHANK)

ST-JSB T101BR

SPEC SHEET



- IDEALLY SUITED
- UNSUITABLE
- OCCASIONAL USE

MATERIALS	
ALUMINIUM	<input type="checkbox"/>
CHIPBOARD	<input checked="" type="checkbox"/>
CONSTRUCTION TIMBER	<input checked="" type="checkbox"/>
FIBRE BOARD (MDF)	<input checked="" type="checkbox"/>
FIBRE CEMENT BOARD	<input type="checkbox"/>
GLASS FIBRE REINFORCED PLASTIC (GRP)	<input type="checkbox"/>
LAMINATE	<input type="checkbox"/>
NAIL EMBEDDED WOOD	<input type="checkbox"/>
NON FERROUS METALS (COPPER, ZINC, LEAD)	<input type="checkbox"/>
PLASTER BOARD	<input type="checkbox"/>
PLASTIC (PVC)	<input checked="" type="checkbox"/>
PLYWOOD	<input checked="" type="checkbox"/>
STEEL SECTION (PIPE, ANGLE, BOX)	<input type="checkbox"/>
STEEL SHEET	<input type="checkbox"/>
WOOD - CLEAN HARDWOOD	<input type="checkbox"/>
WOOD - CLEAN SOFTWOOD	<input checked="" type="checkbox"/>

DESCRIPTION:

Cutting on the down stroke, the ST-JSB T101BR delivers straight cuts, with a smooth, clean finish to the top surface. Cutting materials such as Softwood, plywood, chipboard and Fibre Board (MDF), with a thickness between 3mm and 30mm.

FEATURES:

- Made from High Carbon Steel (HCS)
- Precision-ground teeth, with a Taper-ground body

MACHINE SUITABILITY:

All T-shank Jigaws, inc Makita, Bosch, Dewalt, Festool, Erbauer & Hikoki

USER TIPS:

- Always wear the appropriate PPE
- Ensure you select the correct blade for your task
- Disconnect the power/ remove the battery prior to fitting or removing a blade
- If you have a variable speed Jigsaw, select faster speeds for soft materials, and slower speeds for harder materials such as Steel.
- If your Jigsaw has an oscillating option, this will increase the speed of cut, but reduce the finish quality.
- Always ensure that the foot plate is flat to the surface before cutting
- When starting a cut, make gentle contact with the material, forcing the cut will cause the blade to jump and damage the teeth
- Once you have completed your cut, wait for the blade to stop, before removing from the material
- Blades that cut on the up stroke will leave a feathered edge to the surface of the material, but are smoother and easier to use. Select a reverse cut/ down cut blade to ensure a clean finish to the cutting surface.

PACKAGING DETAILS:

Full colour cardboard sleeve.





PRODUCT DETAILS:

PART NO.	DIMENSIONS
GT42002	T101BR

✉ sales@premierdiamondproducts.co.uk ☎ +44 (0) 1227 711 555

Another quality product from Premier Diamond Products ISO Certified Company



www.premierdiamondproducts.co.uk