

CONCRETE FLOOR GRINDING & COATING REMOVAL SEGMENT SHOES

CONCRETE SHOES:

SPEC SHEET










COARSE/30 GRIT




MEDIUM/60 GRIT











FINE/ 100 GRIT

DESCRIPTION:

The P6-HTC Two segmented floor grinding shoes, with 10mm of usable diamond, are for grinding medium hard concrete surfaces, between 3 and 5 on the Mohs scale. The P6-HTC shoes come in three grit sizes, giving varying degrees of stock removal and finish to the concrete surface.

The P6-HTC PCD shoe is designed for the removal of floor coatings such as flooring adhesives, epoxies and polyurethanes.

FEATURES:

Winged 'knock on' fitting, Long life, Colour coded for easy identification

MACHINE SUITABILITY:

HTC and Husqvarna Floor grinding machines

EN13236: European Standard that regulates the safety requirements for super abrasive (diamond) products.



PACKAGING DETAILS:

Brown corrugated card with label – fully recyclable



PRODUCT DETAILS:

	PART NO.	GRIT SIZE	COLOUR CODE	SEGMENT HEIGHT (MM)	UNIT OF SALE	LIST PRICE
	DP16940	30	Red	10	1	£64.50
	DP16942	60	Blue	10	1	£64.50
	DP16944	100	Green	10	1	£64.50
	DP16946	PCD	Gold	N/A	1	£146.15

PCD

USER TIPS:

- Always wear the appropriate PPE
- Using a plastic hammer, ensure that the shoes are located securely on the mounting plate
- DO NOT use a metal hammer to fit the shoes as this may damage them
- To achieve a clean and level surface, use a smooth left to right sweeping action when grinding and avoid applying any excessive downward pressure
- Once the segments have worn away, remove the shoes by tapping towards the centre of the mounting plate, and recycle the spent shoe at any metal recycling centre



Winged 'knock on' fitting,







